

TECHNICAL SPECIFICATIONS POWER PACK

TECHNICAL DETAILS

METRIC

US/IMPERIAL

BRAND

UGT Hydraulics

Power (kW)	11 kW 15 HP Flash proof Flange Mount
Power Input	3ph 415v
Rev Output	1450 rpm
Weight incl. oil	186 kg 446 lb
Dimensions (LxWxH)	1653x836x871 mm
Oil flow	34 l/min 9 gpm 2000 psi
Maximum pressure	145 bar 2,000 psi
Power On Demand (POD)	Yes "E" Stop Override at Power Pack
Oil Capacity	80 lts 21 Gallons (US)
Filtration	10 micron filter Pressure in-line. Filter by-pass valve in valve block.
Cooling system	Flushing water cooling.
Part number	MPP 4000-4000
Sound power level guaranteed	73 dB(A)
Part Number	(2000/14/EC)

HI Mining power packs currently come in two varieties the fully mobile unit MPP 4000-4000 and our unique tray back cassette TBC 4000-4200.

Our power packs come with remote start and stop capabilities and illuminated override emergency stop buttons located at the unit. We utilize the flushing water circulated through the oil reservoir to cool the oil.

Our tray back cassette unit can be purchased fully optioned with its own water supply and with the convenience of being rechargeable allows for hydraulic energy where ever it is required.

We can also manufacture power packs to suit individual requirements.



57a Division St, Welshpool W.A 6106 | Ph: +61 08 9255 1065
E: info@himiningglobal.com | www.himiningglobal.com